

ITA/AITES

TRAINING MATERIAL

SETTLEMENTS INDUCED BY TUNNELING IN SOFT GROUND

Prepared by WG. 2 “Maintenance and Repair”

Animateur: E. Leca (France)

2007

Index

1

Introduction

2

Chapter 1 - Tunneling Induced Ground Movements

3

Chapter 2 - Causes For Construction Induced Settlements

4

Chapter 3 - Evaluation of Ground Movements

5

Chapter 4 - Incidence of Ground Displacements on Existing Structures

6

Chapter 5 – Settlement Control

7

Chapter 6 – Observation and Monitoring of Ground Response

8

Chapter 7 – Contractual Aspects

9

Future Developments and References

Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6

7

8

9

Ground motion induced by tunneling and impact on existing structures

Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6

7



8

9

Tunneling Induced Ground Movements


Settlements Induced by Tunneling in Soft Ground

Displacements of the Excavation Profiles




Settlements Induced by Tunneling in Soft Ground

Yielding Zone Around the Opening




a. Limited extension

b. Weaker grounds




Settlements Induced by Tunneling in Soft Ground

Tunnel Face Stability




a. Clayey Grounds




Settlements Induced by Tunneling in Soft Ground

Tunnel Face Stability




b. Frictional Grounds




Settlements Induced by Tunneling in Soft Ground

Tunnel Face Stability




- Clayey Grounds:
 - $N = (\sigma_s + \gamma H - \sigma_T) / S_u$
 - $N < 5-6$
 - U- shear strength: S_u
- Frictional Grounds:
 - $\sigma_s / \sigma_c, \gamma D / \sigma_c, \sigma_T / \sigma_c$
 - $\sigma_c = 2c' \cos \phi' / (1 - \sin \phi')$
 - Cohesion: c'
 - Friction angle: ϕ'




Settlements Induced by Tunneling in Soft Ground

Propagation of Movements Towards the Surface




a. Deeper Tunnel




Settlements Induced by Tunneling in Soft Ground

Propagation of Movements Towards the Surface




b. Shallow Tunnel



Settlements Induced by Tunneling in Soft Ground

Influence of Support Conditions





- Support stiffness
- Installation timeframe



Settlements Induced by Tunneling in Soft Ground

Surface Settlement Trough



Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6

7

8


9

Causes For Construction Induced Settlements



Settlements Induced by Tunneling in Soft Ground

Main Sources For Settlements (sequential construction)

- Face intake/instability
- Impact of characteristics and installation conditions of temporary support
- Staging of the excavation works (cross-section)
- Final liner installation and response




Settlements Along a Shield Driven Tunnel



Settlements Induced by Tunneling in Soft Ground

Typical Contributions to Shield Tunneling Induced Settlements


- Face intake: 10-20%
- Along the shield: 40-50%
- Tail skin: 30-40%



Settlements Induced by Tunneling in Soft Ground

Sources For Additional Settlements

- Effect of groundwater
 - During construction
 - drawdown of ground water table
 - Seepage towards the tunnel face
 - In the long term (consolidation)
- Effect of worksite conditions
 - e.g. impact of vibrations of weaker grounds



Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6

7

8


9

Evaluation of Ground Movements


Settlements Induced by Tunneling in Soft Ground

Settlement Evaluation Methods


- Empirical and Semi-empirical
 - Analytical
 - Observational
- Numerical




Settlement Trough Characterization



3D Distribution




Cross-section



Settlements Induced by Tunneling in Soft Ground

Settlement Trough Characterization



$$s(x) = s_{max} \cdot \exp(-x^2/2i^2)$$

$$V_s = (2\pi)^{1/2} \cdot i \cdot s_{max}$$


Key parameters: s_{max} , i

(Peck, Schmidt, 1969)



Settlements Induced by Tunneling in Soft Ground

Dampening Effect



- V_l = Volume loss at the opening
- V_s = Volume loss at ground level




Settlements Induced by Tunneling in Soft Ground

Ground Movements at Depth

- $S(x,z)=s_{\max}(z).\exp(-x^2/2(Kz)^2)$
- $H(x,z)=S(x,z).x/z$
- $V_s(z)=(2\pi)^{1/2}.Kz.s_{\max}(z)$
- K = empirical coefficient
 - (varies typically from 0.5 for stiff clay and sandy clay to 0.25 to softer sands and gravels)

(after O'Reilly & New, 1982)



Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6


7

8

9

Incidence of Ground Displacements on Existing Structures

Settlements Induced by Tunneling in Soft Ground




Typical Idealized Building Response to Ground Motion

(after Attewell et al, 1986)



Settlements Induced by Tunneling in Soft Ground

Induced Vertical Movements



ρ_{vA} = settlement at A

δ_{vAB} = differential settlement
b/w A-B

ω = tilt

β_{BC} = relative rotation b/w B-C

α_C = angular deformation at C


Δ_{AD} = relative deflection b/w A-D

Δ_{AD}/L_{AD} = deflection rate



Settlements Induced by Tunneling in Soft Ground



Induced Horizontal Movements



$$\epsilon_{hAB} = (\rho_{hA} - \rho_{hB}) / L_{AB}$$

Settlements Induced by Tunneling in Soft Ground

Induced Horizontal Deformations



Settlements Induced by Tunneling in Soft Ground

Damage Classification

<u>Damage Type</u>	<u>Damage Degree</u>	<u>Damage Description</u>	<u>Crack width (mm)</u>
0	Negligible	Micro-cracks	<0.1
1	Very slight	Architectural	<1
2	Slight	Archit. - to treat	<5
3	Moderate	Functional	5-15 or sev.>3
4	Severe	Structural	15-25 (number)
5	Very severe	Structural	>25 (number)


(after Burland et al, 1977; Burland, 1995; Mair et al, 1996)

Settlements Induced by Tunneling in Soft Ground

Relationship Between Critical Extension and Cracking

Damage Type	0	1	2	3	4&5
$\varepsilon_{\text{crit}} (\%)$	≤ 0.050	$0.050 < \leq 0.075$	$0.075 < \leq 0.150$	$0.150 < \leq 0.300$	$0.300 <$


(after Boscardin & Cording, 1989)



Settlements Induced by Tunneling in Soft Ground

Range of Serviceability Limit State For Standard Structures

Damage Type	Average Slope of Settlement Trough Under Structure (%)	Maximum Settlement of the Structure (mm)
1	< 2	< 10
2	$2 < < 4$	$10 < < 20$



Design Methodology

- Phase 1: Investigation of Existing Buildings
- Phase 2: Information Summary
- Phase 3: Selection of Damage Criteria
- Phase 4: Modeling (after Burland, 1995; Mair et al, 1996)
 - Preliminary Assessment
 - Second Stage Assessment
 - Detailed Evaluation
- Phase 5: Determination of Allowable Thresholds
- Phase 6: Back-analysis & Calibration of Models



Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6

7

8


9

Settlement Control

Settlements Induced by Tunneling in Soft Ground


Preventive & Remedial Approaches

1. Improvement of Overall Project Conditions
 - Aim at larger depth of cover
 - Look for ground layers of good mechanical properties
 - Minimize excavated cross-section
 - Aim at straight alignments
2. Improvement of Ground Characteristics
3. Structural Improvement of Building
4. Improvement During Construction
 - a. Sequential/Conventional
 - b. Shield Tunneling




Settlements Induced by Tunneling in Soft Ground

Pre-support




Face Bolting




Settlements Induced by Tunneling in Soft Ground

Pre-support




Fore-poling




Settlements Induced by Tunneling in Soft Ground

Pre-support




Umbrella Vault




Settlements Induced by Tunneling in Soft Ground

Pre-support




Pre-vault



Settlements Induced by Tunneling in Soft Ground



Crown Support



Expanded Concrete Segment Vault

Settlements Induced by Tunneling in Soft Ground

Underpinning



Settlements Induced by Tunneling in Soft Ground

1

2

3

4

5

6

7

8


9

Observation and Monitoring of Ground Response

Settlements Induced by Tunneling in Soft Ground

Observation & Monitoring

- Inspection
- Instrumentation
 - Monitoring of existing structures
 - Ground measurements
- Monitoring Program



1

2

3

4

5

6

7

8


9

Contractual Aspects

Settlements Induced by Tunneling in Soft Ground

Contractual Aspects

- Usual contractual clauses
- Position of the different players
 - The Owner
 - The Engineer
 - The Contractor



1

2

3

4

5

6

7

8


9

Further Developments and References

Settlements Induced by Tunneling in Soft Ground


Recommendations and Possible Ways of Improvement

- At Owner – and Engineer - Level
 - Organize preliminary inspections & studies
 - Commission a comprehensive program of studies
 - Set appropriate settlement limits
 - Provide available information at tender stage
- At Contractor's Level
 - Provide assistance required during construction
 - Set accountabilities
- Possible contribution of Insurance Companies
 - Obtain greater technical clarity when defending cases
 - Require risk analyses prior to finalizing binding agreements
 - Exercise greater diligence when reviewing litigious situations



References

- AITES-ITA, Working Group 2: Leca, E. & New, B., “Settlements induced by tunneling in Soft Ground”, Tunnelling and Underground Space Technology (TUST) 2007, 22, Nr. 2, 119-149.
- AFTES, Groupe de Travail n°16 : Leblais, Y., André, D., Dubois, P., Gigan, J.P., Guillaume, J., Leca, E., Pantet, A., Riondy, G., 1994, « Tassements liés au creusement d’ouvrages souterrains », Tunnels et Ouvrages Souterrains (TOS), 132.
- Additional references quoted in WG2 document (TUST, 22)



Clause de non-responsabilité pour les rapports des groupes de travail de l'AITES

L'Association Internationale des Travaux en Souterrain (AITES) publie ce rapport, conformément à ses Statuts, pour faciliter les échanges d'informations afin :

d'encourager l'utilisation du sous-sol au profit du grand public, de l'environnement et du développement durable;

de promouvoir les progrès dans la planification, le projet, la construction, l'entretien, la réhabilitation et la sécurité des tunnels et de l'espace souterrain en rassemblant et confrontant les informations, ainsi qu'en étudiant les questions qui s'y rapportent.

Cependant, l'AITES décline toute responsabilité en ce qui concerne les informations publiées dans ce rapport.

Ces informations :

sont exclusivement de nature générale et ne visent pas la situation particulière d'une personne physique ou morale;

ne sont pas nécessairement complètes, exhaustives, exactes ou à jour ;

proviennent parfois de sources extérieures sur lesquelles les services de l'AITES n'ont aucun contrôle et pour lesquelles l'AITES décline toute responsabilité ;

ne constituent pas un avis professionnel ou juridique (si vous avez besoin d'avis spécifiques, consultez toujours un professionnel dûment qualifié).

Disclaimer for the reports of ITA working groups

The International Tunnelling Association (ITA) publishes this report to, in accordance with its statutes, facilitate the exchange of information, in order:

to encourage planning of the subsurface for the benefit of the public, environment and sustainable development

to promote advances in planning, design, construction, maintenance and safety of tunnels and underground space, by bringing together information thereon and by studying questions related thereto.

However ITA accepts no responsibility or liability whatsoever with regard to the material published in this report.

This material is:

information of a general nature only, which is not intended to address the specific circumstances of any particular individual or entity;

not necessarily comprehensive, complete, accurate or up to date;

sometimes collected from external sources over which ITA services have no control and for which ITA assumes no responsibility;

not professional or legal advice (if you need specific advice, you should always consult a suitably qualified professional).

